

Technical data sheet



11-2015

Film T100 2x50 m ECO

Item no: 201
Scope of application: Universal film for protection against wind, moisture and pollution.

Technical specification:

Product material:	LDPE		
Colour:	grey - black		
Density:	0,981-0,924	g/cm ³	
Width:	2,00 (+/- 1 %)	m	EN 1848-2
Length:	50,00 (+/- 1 %)	m	EN 1848-2
Thickness:	40 (+/- 5 %)	μ	EN 1849-2
Tensile strength (longitudinal):	≥ 45	N/50 mm	EN 12311-2
Tensile strength (transversal):	≥ 41	N/50 mm	EN 12311-2
Elongation (longitudinal):	≥ 700	%	EN 12311-2
Elongation (transversal):	≥ 630	%	EN 12311-2
Tear resistance (longitudinal):	≥ 9,0	N	EN 12310-2
Tear resistance (transversal):	≥ 7,0	N	EN 12310-2
UV stabilization:	no	-	
Melting point:	110 - 150	°C	
Melt-mass-flow rate (MFR):	0,34 - 1,1	g/10/min, 190°C, 2,16 kg	

Packing:

Roll width:	1,00	m
Content (roll/pallet):	132	rolls
Dimensions - pallet:	800 x 1.200	mm
Storage:	Store cool and dry	

General information:

This data sheet supersedes all previous editions. The information contained in this technical data sheet corresponds to our current knowledge and experience of application. The information has been carefully and conscientiously created, but without responsibility for its accuracy or completeness and no liability for the subsequent decisions of the user. The information on its own create any legal obligation or any other ancillary obligations. The user is in principle obliged to check the product independently to its suitability for the foreseen use.

Our products are subjected, like all raw materials contained, continuous monitoring, whereby a constant quality is ensured. Changes in the information contained in this leaflet, we reserve at any time.

Distribution:

Lorencic GmbH Nfg. & Co KG
Puchstraße 208
8055 Graz
Telefon: +43 316 47 25 64-0
Fax: +43 316 47 25 64-77
e-Mail: headquarters@lorencic.com